




LOOK™ Inner Etched Integrated LED Backlit Mirror

Part Number | 69455.XXXX.YYYY.RMT
Please see specifications for part configurations


Features

- Improved illumination and reduced shadowing through the use of side lighting
- Illumination from the back provides an ambient glow
- Mirror and mounting panel is IP44 rated
- Detailed dimensional drawings are available for all mirrors to help in planning the layout of blocking and power supply location.
- Safety PVC membrane on back prevents small pieces from falling off in the event of a mirror breakage
- Lead free silver backing exceeds ISO 9227:2012, 120 hour corrosion testing
- Can be mounted either portrait or landscape orientation
- Back box power supply provides flexible installation that meets stringent building codes
- Power supply junction box can be screwed into the pre-installed brackets on the mirror or into contractor supplied blocking



Inner Etched Options

69455.3927.30K.RMT




Dimensions	39.4"H x 27.6"W x 2"D
Housing	Anodized Aluminum
Lens	Glass
Wattage	34W @ 120V AC
Voltage	120 -277V AC
Current	0.28A @ 120V AC
Lumens	2450 LM @ 120V AC
Kelvin	3000K or 4000K ²
CRI	> 90
Efficacy	72 LM/W @ 120V AC

69455.2424.30K.RMT



Dimensions	23.6"W x 23.6"H x 1.8"D
Housing	Anodized Aluminum
Lens	Glass
Wattage	25W @ 120V AC
Voltage	120 - 277V AC
Current	0.21A @ 120V AC
Lumens	1630 LM @ 120V AC
Kelvin	3000K or 4000K ²
CRI	> 90
Efficacy	65 LM/W @ 120V AC


69455.CIR.24.30K.RMT



Dimensions	23.6" Diameter x 1.8"D
Housing	Anodized Aluminum
Lens	Glass
Wattage	21W @ 120V AC
Voltage	120 - 277V AC
Current	0.18A @ 120V AC
Lumens	1430 LM @ 120V AC
Kelvin	3000K or 4000K ²
CRI	> 90
Efficacy	68 LM/W @ 120V AC

Power Box Specifications

*Ordered Separately



Part Number 690010.121

Dimensions 13"L x 1.25"W x 1.7"D

Housing Aluminum

Wattage 28.8W

Voltage 120 - 277V AC

Current MAX 1.3A

Power Factor 0.99 @120VAC
0.95 @277VAC

Frequency 47 - 63Hz

Efficacy 85% @120VAC
88% @277VAC

Notes:

1. Lumens per watt based on light source
2. Standard non-stock mirrors subject to 90 day lead time
3. Custom mirrors available upon request, subject to a 50 piece minimum, 50% deposit and 90 day lead time following approved drawings
4. Mirrors must be shipped LTL and cannot be shipped via FedEx or UPS